

Boxed In (4.5" squares)



Simple Five Quilts
Quilts Made from 5" squares
Approximate Finished Size 40" x 48"

Boxed In (4.5" squares)



Simple Five Quilts
Quilts Made from 5" squares
Approximate Finished Size 40" x 48"

Boxed In (4.5" squares)



Simple Five Quilts
Quilts Made from 5" squares
Approximate Finished Size 40" x 48"

Boxed In (4.5" squares)



Simple Five Quilts
Quilts Made from 5" squares
Approximate Finished Size 40" x 48"

Materials Needed

- 92 - 4.5" squares
- $\frac{5}{8}$ yard of fabric for sashing

Instructions for Cutting the Sashing Fabric

Cut the sashing fabric into:

- 8 - 2 $\frac{1}{2}$ " \times width of the fabric strips
- Subcut the strips as follows*:
 - 2 - 2 $\frac{1}{2}$ " \times 24 $\frac{1}{2}$ " rectangles for side inner sashing
 - 2 - 2 $\frac{1}{2}$ " \times 20 $\frac{1}{2}$ " rectangles for top and bottom inner sashing
 - 2 - 2 $\frac{1}{2}$ " \times 36 $\frac{1}{2}$ " rectangles for side outer sashing
 - 2 - 2 $\frac{1}{2}$ " \times 32 $\frac{1}{2}$ " rectangles for top and bottom outer sashing
- * Please confirm the lengths before cutting and adjust the lengths as necessary.

Assembling the Quilt

- Use the picture on the front of the card as a guide to assembling the quilt. Work from the center outward.
- Note: Each time sashing is added, be sure to add the side sashings before the top and bottom sashings.

Materials Needed

- 92 - 4.5" squares
- $\frac{5}{8}$ yard of fabric for sashing

Instructions for Cutting the Sashing Fabric

Cut the sashing fabric into:

- 8 - 2 $\frac{1}{2}$ " \times width of the fabric strips
- Subcut the strips as follows*:
 - 2 - 2 $\frac{1}{2}$ " \times 24 $\frac{1}{2}$ " rectangles for side inner sashing
 - 2 - 2 $\frac{1}{2}$ " \times 20 $\frac{1}{2}$ " rectangles for top and bottom inner sashing
 - 2 - 2 $\frac{1}{2}$ " \times 36 $\frac{1}{2}$ " rectangles for side outer sashing
 - 2 - 2 $\frac{1}{2}$ " \times 32 $\frac{1}{2}$ " rectangles for top and bottom outer sashing
- * Please confirm the lengths before cutting and adjust the lengths as necessary.

Assembling the Quilt

- Use the picture on the front of the card as a guide to assembling the quilt. Work from the center outward.
- Note: Each time sashing is added, be sure to add the side sashings before the top and bottom sashings.

Materials Needed

- 92 - 4.5" squares
- $\frac{5}{8}$ yard of fabric for sashing

Instructions for Cutting the Sashing Fabric

Cut the sashing fabric into:

- 8 - 2 $\frac{1}{2}$ " \times width of the fabric strips
- Subcut the strips as follows*:
 - 2 - 2 $\frac{1}{2}$ " \times 24 $\frac{1}{2}$ " rectangles for side inner sashing
 - 2 - 2 $\frac{1}{2}$ " \times 20 $\frac{1}{2}$ " rectangles for top and bottom inner sashing
 - 2 - 2 $\frac{1}{2}$ " \times 36 $\frac{1}{2}$ " rectangles for side outer sashing
 - 2 - 2 $\frac{1}{2}$ " \times 32 $\frac{1}{2}$ " rectangles for top and bottom outer sashing
- * Please confirm the lengths before cutting and adjust the lengths as necessary.

Assembling the Quilt

- Use the picture on the front of the card as a guide to assembling the quilt. Work from the center outward.
- Note: Each time sashing is added, be sure to add the side sashings before the top and bottom sashings.

Materials Needed

- 92 - 4.5" squares
- $\frac{5}{8}$ yard of fabric for sashing

Instructions for Cutting the Sashing Fabric

Cut the sashing fabric into:

- 8 - 2 $\frac{1}{2}$ " \times width of the fabric strips
- Subcut the strips as follows*:
 - 2 - 2 $\frac{1}{2}$ " \times 24 $\frac{1}{2}$ " rectangles for side inner sashing
 - 2 - 2 $\frac{1}{2}$ " \times 20 $\frac{1}{2}$ " rectangles for top and bottom inner sashing
 - 2 - 2 $\frac{1}{2}$ " \times 36 $\frac{1}{2}$ " rectangles for side outer sashing
 - 2 - 2 $\frac{1}{2}$ " \times 32 $\frac{1}{2}$ " rectangles for top and bottom outer sashing
- * Please confirm the lengths before cutting and adjust the lengths as necessary.

Assembling the Quilt

- Use the picture on the front of the card as a guide to assembling the quilt. Work from the center outward.
- Note: Each time sashing is added, be sure to add the side sashings before the top and bottom sashings.